



"Passionately Protecting Mother-Nature since 1978"

Estd. Since 1978

# Bharat Oil Company (I) Regd.

Recycling & Incineration of Hazardous Wastes

ISO 9001-2015



Lube Oil Re-Refining & Wholesale of Industrial Lubricating Oils

Hazardous & E-Waste Management

Incineration, Pre-Processing of Waste

WTS™ - Enterprise Waste Tracking & Management Software

Regd with MoeF&CC / CPCB as Recycler & Reprocessor

Authorised by UPPCB, for Lube Oil Recycling, HW & E-Waste Management

SEPL™. NABL Accredited Laboratory for Testing of Air, Water, Soil, Hazardous Waste / Sludge / Slurry / Soil / Sediments / Chemicals/Materials

## Specifications of Gear Oil ISO (VG 150)

| Parameters  | Result  |
|---|---------|
| Viscosity @ 40°C (cSt)                            | 135     |
| Viscosity Index:                                  | 90      |
| Flash Point (COC):                                | 213°C   |
| Pour Point:                                       | - 2°C   |
| Copper Corrosion Test (3 hrs. @ 100°C):           | 1b      |
| Demulsibility Test @ 54°C (40/37/3 ml in 30 min): | 40-38-2 |

**Application** - Gear oil ISO VG 150 is a medium-viscosity lubricating oil mainly used for industrial gear systems operating under moderate loads and speeds like (industrial Gearboxes, Bearings, and Couplings)



**Regd. & Sales/Corporate Office:**  
Building No. 11, LGF, Community Centre,  
East of Kailash, New Delhi - 110065, India  
Ph : 011-41000710, 26210205, 26216466

**Facilities:**  
E - 18, Sahibabad Industrial Area, Site 4,  
Ghaziabad - 201010, UP, India

Sales/WhatsApp : +91-9717706048  
Email : sales@bharatoil.com, Website : www.bharatoil.com

