



"Passionately Protecting Mother-Nature since 1978"

Estd. Since 1978

Bharat Oil Company (I) Regd.

Recycling & Incineration of Hazardous Wastes

ISO 9001-2015



Quality Certified Company

Lube Oil Re-Refining
& Wholesale of
Industrial Lubricating Oils

Hazardous
& E-Waste
Management

Incineration,
Pre-Processing
of Waste

WTS™ - Enterprise
Waste Tracking &
Management Software

Regd with
MoEF&CC / CPCB
as Recycler & Reprocessor

Authorised by UPPCB,
for Lube Oil Recycling,
HW & E-Waste Management

SEPL™ - NABL Accredited Laboratory for Testing of Air,
Water, Soil, Hazardous Waste / Sludge / Slurry / Soil
/ Sediments / Chemicals/Materials

Specifications of Hydraulic Oil ISO (VG-68)

Parameters / Details	Result
SAE Grade	Hydraulic oil -68
Density @ 15°C	864kg/m ³
Kinematic Viscosity @ 100°C	10.1 mm ² /s
Kinematic Viscosity @ 40°C	65.31 mm ² /s
Flash Point (COC)	210°C
Pour Point	-15°C
Performance Standards	API CG-4/CF, ACEA E2 (level)

Application - Hydraulic presses, injection moulding machines, Machine tools Elevators and lifts, Power steering systems, Hydraulic brakes (specific fluids, not regular hydraulic oil) Forklifts, cranes, and other material handling equipment.



Regd. & Sales/Corporate Office:
Building No. 11, LGF, Community Centre,
East of Kailash, New Delhi - 110065, India
Ph : 011-41000710, 26210205, 26216466

Facilities:
E - 18, Sahibabad Industrial Area, Site 4,
Ghaziabad - 201010, UP, India

Sales/WhatsApp : +91-9717706048
Email : sales@bharatoil.com, Website : www.bharatoil.com

