



"Passionately Protecting Mother-Nature since 1978"

Estd. Since 1978

ISO 9001-2015



Quality Certified Company

Bharat Oil Company (I) Regd.

Recycling & Incineration of Hazardous Wastes

Lube Oil Re-Refining
& Wholesale of
Industrial Lubricating Oils

Hazardous
& E-Waste
Management

Incineration,
Pre-Processing
of Waste

WTS™ - Enterprise
Waste Tracking &
Management Software

Regd with
MoeF&CC / CPCB
as Recycler & Reprocessor


Authorised by UPPCB,
for Lube Oil Recycling,
HW & E-Waste Management

SEPL™- NABL Accredited Laboratory for Testing of Air,
Water, Soil, Hazardous Waste / Sludge / Slurry / Soil
/ Sediments / Chemicals/Materials

Specification of Re-Refined Transformer Oil

Parameters	Result
Appearance	Clear
Color	0.5ASTM
Viscosity @ 40°C	3.7 cSt
Density	0.88 gm/cc
Flash Point (COC):	158°C
Pour Point:	- 5°C
Water Content	Nil

Application - Re-refined transformer oil is produced by reclaiming used mineral insulating oils through physical and chemical processes to restore its electrical, chemical, and physical properties close to those of virgin mineral oil. It is suitable for use in power transformers, distribution transformers, and other electrical equipment.



Regd. & Sales/Corporate Office:
Building No. 11, LGF, Community Centre,
East of Kailash, New Delhi - 110065, India
Ph : 011-41000710, 26210205, 26216466

Facilities:
E - 18, Sahibabad Industrial Area, Site 4,
Ghaziabad - 201010, UP, India

Sales/WhatsApp : +91-9717706048
Email : sales@bharatoil.com, Website : www.bharatoil.com

