



# Bharat Oil Company (I) Regd.

Recycling & Incineration of Hazardous Wastes

ISO 9001-2015



Lube Oil Re-Refining  
& Wholesale of  
Industrial Lubricating Oils

Hazardous  
& E-Waste  
Management

Incineration,  
Pre-Processing  
of Waste

WTS™ - Enterprise  
Waste Tracking &  
Management Software

Regd with  
MoEF&CC / CPCB  
as Recycler & Reprocessor

Authorised by UPPCB,  
for Lube Oil Recycling,  
HW & E-Waste Management

SEPL™ - NABL Accredited Laboratory for Testing of Air,  
Water, Soil, Hazardous Waste / Sludge / Slurry / Soil  
/ Sediments / Chemicals/Materials

## Specifications of Shuttering Oil

Parameters / Details	Result
SAE Grade	SHUTTERING OIL
Density @ 29.5°C	0.810 gm/cc
Kinematic Viscosity @ 40°C	26.4 mm <sup>2</sup> /s
Kinematic Viscosity @ 100 °C	3.5 mm <sup>2</sup> /s
Flash Point (COC)	154°C
Pour Point	-3°C
Application	Steel shuttering wooden plywood loam works



Regd. & Sales/Corporate Office:  
Building No. 11, LGF, Community Centre,  
East of Kailash, New Delhi - 110065, India  
Ph : 011-41000710, 26210205, 26216466

Facilities:  
E - 18, Sahibabad Industrial Area, Site 4,  
Ghaziabad - 201010, UP, India

Sales/WhatsApp : +91-9717706048

Email : sales@bharatoil.com, Website : www.bharatoil.com

