



"Passionately Protecting Mother-Nature since 1978"

Estd. Since 1978

Bharat Oil Company (I) Regd.

Recycling & Incineration of Hazardous Wastes

ISO 9001-2015



Quality Certified Company

Lube Oil Re-Refining
& Wholesale of
Industrial Lubricating Oils

Hazardous
& E-Waste
Management

Incineration,
Pre-Processing
of Waste

WTS™ - Enterprise
Waste Tracking &
Management Software

Regd with
MoeF&CC / CPCB
as Recycler & Reprocessor

Authorised by UPPCB,
for Lube Oil Recycling,
HW & E-Waste Management

SEPL™ - NABL Accredited Laboratory for Testing of Air,
Water, Soil, Hazardous Waste / Sludge / Slurry / Soil
/ Sediments / Chemicals/Materials

Specifications of Transmission Oil SAE Grade – (80W-90)

Parameters / Details	Result
SAE Grade	80W-90
Density @ 15°C	0.875 gm/cc
Kinematic Viscosity @ 40°C	154 mm ² /s
Kinematic Viscosity @100 °C	15.4 mm ² /s
Flash Point (COC)	208°C
Pour Point	-10°C
Sulphated Ash Content	1.46% wt.
Performance Standards	API CG-4/CF, ACEA E2 (level)
Application	Reduces friction and wear between gears, shafts, bearings, and other moving parts inside the transmission.



Regd. & Sales/Corporate Office:
Building No. 11, LGF, Community Centre,
East of Kailash, New Delhi - 110065, India
Ph : 011-41000710, 26210205, 26216466

Facilities:
E - 18, Sahibabad Industrial Area, Site 4,
Ghaziabad - 201010, UP, India

Sales/WhatsApp : +91-9717706048

Email : sales@bharatoil.com, Website : www.bharatoil.com

